

XE-MINI/ED PLUS SERIES

ELECTRIC SELF-PROPELLED MINI SCISSOR LIFT

Standard Features

- Proportional Controls
- Self-lock gate on platform
- Extended Platform
- Drivable at full height
- Non-marking Tires
- 4*2WD
- Automatic brake system
- Emergency lowering system
- Emergency stop button
- Explosion-proof of the tubing
- Diagnosis system
- Tilt sensor with Alarm
- Horn
- Flash light
- Hour meter
- Safety Brackets
- Forklift Pockets

Option Features

- Overload sensor
- AC power to platform
- Pothole Guards



XE-MINI PLUS SERIES

Model	XE50MINI/ED PLUS	XE60MINI/ED PLUS
Working height max(m)	5	6.4
Platform height max(m)	3	4.4
Outreach(m)	0.55	0.55
Lifting capacity(kg)	240	240
Lifting capacity(kg)(Extended platform)	100	100
Weight(kg)	760	810
Platform size(L x W x H)m	1.28X0.76X1.1	1.28X0.76X1.1
The length of platform extended(m)	1.8	1.8
Skirting board height(m)	0.17	0.17
Stowed size(L x W)m	1.49X0.76	1.49X0.76
Stowed height(m)	2.03	2.03
Height of the machine with platform folded(m)	1.5	1.59
Hydraulic tank capacity(L)	2	2
Gradeability	25%	25%
Wheelbase(m)	1	1
Ground clearance(m)	0.06	0.06
Inside rotation radius(m)	0.35m	0.35m
Load number max	2	2
Raised time/Lowering time(s)	20/17	23/19
Traction speed(km/h)	3	3
Safe speed(km/h)	0.8	0.8
Vertical tilt°	3	3
Lateral tilt°	2	2
Power source	24V	24V
Tire size(mm)	Solid Non-marking tires 230	Solid Non-marking tires 230

